

1040 liter tank i Syrafast 316



273 000 SEK /st exkl moms

Additional information: Fully comprehensive documentation in accordance with pharmaceutical industry standards included in the scope of delivery; device was manufactured for a global pharmaceutical company but never put into operation there; hand hole with sight glass diameter: 150 mm; incl. Südmo single seat valve SVP (outlet)

Volumetric volume (L): 1.040 L

Pressure in tank: vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 42 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Top: 8 mm

Cylinder: 5 mm

Bottom: 6 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.200 mm

Cylinder height: 1.330 mm

Total height of tank: 2.350 mm

Empty weight tank: 1.050

SKU: 441170

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Full set of pharma-compliant technical documentation included in delivery; tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass

Övrig information2: diameter: 150mm; incl. Südmo single-seat valve SVP (outlet); we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1040

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.330 mm
Invändig diameter: 1.000 mm
Total höjd: 2.350 mm
Ytterdiameter: 1.200 mm

Tjocklek på tank

Botten: 6 mm
Cylinder: 5 mm
Topp: 8 mm

Mer

Isolerad: Ja
Vikt: 1.050