

1000 liter tank i Syrafast 316



302,000,00 kr /st exkl moms

Additional information: Tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 285mm; incl. Südmo single-seat valve SVP (outlet)

Volumetric volume (L): 1.000 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 60 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Top: 4,50 mm

Cylinder: 6 mm

Bottom: 4 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.194 mm

Cylinder height: 1.332 mm

Empty weight tank: 800

SKU: 458252



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 285mm; incl. Südmo single-seat valve SVP (outlet); we can't give any

Övrig information2: guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.332 mm

Invändig diameter: 1.000 mm

Ytterdiameter: 1.194 mm

Tjocklek på tank

Botten: 4 mm

Cylinder: 6 mm

Topp: 4,50 mm

Mer

Isolerad: Ja

Vikt: 800